NG TECHNOLO



TEST REPORT

Applicant:

AE TOOL LTD

Address:

Unit B, 11/F. Chung Pont Commercial Building, 300 Hennessy Road, Wanchai, Hong

Kong

The following sample(s) was/were submitted and identified on behalf of the client as:

Product name:

Battery Electrical System Analyser

Model:

BESA-12, ALB40034, BETATB12V, AC5244, LABSE

BESA-12P, 12-1015, BAT Plus, BST-12, BST 760, MBT1015, RBA650, XP600

BESA-12PM, BESA-12G, RBAG700, MT 1.2 PRO

Manufacturer:

AE TOOL LTD

Address:

Unit B, 11/F. Chung Pont Commercial Building, 300 Hennessy Road, Wanchai, Hong

Kong

Sample Received

Date:

Jan. 22, 2015

Testing Period

Jan. 22, 2015~ Jan. 28, 2015

Test Requirement and Conclusion: Please refer to the following page(s);

Test Result(s): Please refer to the following page(s);

Tested by	Carlly	Reviewed by:	# APPROVED S		
Approved by:	Monte lino	Date:	2015-01-28		

Shenzhen NTEK Testing Technology Co., Ltd.

1. Product Description

Product Weight, g	556.7
Category under the WEEE	Hor againment
directive	User equipment

Conclusion: When tested as specified, the results shown on the report do not exceed the Reuse/Recycling/Recovery Rate of Directive 2012/19/EU released on EU Official Journal (OJ).

2. Assessment Requirement


As specified by client, to assess the reuse/recycle/recovery of the submitted sample under article 11 and Annex V of Directive 2012/19/EU*

=July 24, 2012, the EU Official Journal (OJ) released the Directive 2012/19/EU which as a new version of WEEE Directive (2002/96/EC). The revised directive has entered into force on the twentieth day after its publication in the OJ.

3. Result of Reuse/Recycling/Recovery Assessments

Reuse/Recycling/Recovery	Reuse/Recycling Rate (%)	Recovery Rate (%)	
Reuse/Recycling/Recovery Target of Products Under WEEE Directive	65	75	
Result of Assessment	82.6	82.6	
WEEE Compliance	Pass	Pass	

4. Appearance of the Product



Shenzhen NTEK Testing Technology Co., Ltd.

Address: 1/F, Building E, Fenda Science Park, Sanwel Community, Xixiang Street, Bao'an District, Shenzhen P.R. China. Tel: (86)-0755-61156588 Fax: (86)-0755-61156599 Http: www.ntek.org.cn



5. Disassembly Assessment

5.1 Disassembly Procedure


The product is disassembled into different parts and grouped by the type of material sharing common characteristic (such as plastic, metal, glass) based on the treatment requirements as set out in the WEEE Directive, followed by the current state of the art of recycling and recovery technology. In addition, the recycling is subject to the economic feasibility, disassembly tools, only bigger parts that can be easily separated are included in the recycling and reuse calculation. Other parts, respectively materials that cannot be separated by e.g. standard tools are classified as either unspecified materials or distributed to the relative waste fraction is expected with recovery rate.

Report No.: NTEK-2015NT0120276R

5.2 Disassembly Time

35 seconds

5.3 Disassembly Tree





6. Selective Treatment for Materials and Components

According to Article 8(2) and the Annex VII of the WEEE Directive, this product contains components and materials items are described in the following table.

Component/Material	Photo No.	Size/Model	Quantity	Weight (g)
LCD	Е	6.5cm×7.0cm	1	38.7
PCB1	F	7.0cm×5.0cm	1	16.6
PCB2	G	12.0cm×8.0cm	1	85.4

7. Material Recycling Information

7.1 Material Reuse/Recycling and Recovery Table

Photo No.	Component / Material Composition	Weight (g)	Percent Weight (%)	Reuse / Recycling Rate(%)	Energy Recovery Rate(%)	Recovery Rate(%)
Α	Metal parts	6.8	1.2	1.2	/	1.2
В	Plastic parts	201.6	36.2	32.2	/	32.2
С	Wire	173.8	31.2	24.7		24.7
D	Metal+Plastic	33.8	6.1	5.2		5.2
Е	LCD	38.7	7.0	5.0		5.0
F	PCB1	16.6	3.0	2.3	1	2.3
G	PCB2	85.4	15.3	12.0		12.0
	Total	556.7	100.0	82.6	/	82.6

Note: Plastic containing brominated flame retardants is not assessed in the list

7.2 Reuse/Recycling and Recovery Rate Calculation

·Calculation Method				
Product total weight	a (g)			
Weight of components, sub-assemblies and consumables	h (-)			
which are reused for their original purpose or recycled.	b (g)			
Weight of materials or components where energy is	- (-)			
recovered through incineration.	c (g)			
Reuse / Recycling Rate	b/a *100 (%)			
Recovery Rate	(b+c)/a *100 (%)			

Shenzhen NTEK Testing Technology Co., Ltd.



8. ANNEX VII of WEEE Directive (2012/19/EU)

Selective treatment for materials and components of waste electrical and electronic equipment referred to in Article 8(2)

As a minimum the following substances, mixtures and components have to be removed from any separately collected WEEE

- —polychlorinated biphenyls (PCB) containing capacitors in accordance with Council Directive 96/59/EC of 16 September 1996 on the disposal of polychlorinated biphenyls and polychlorinated terphenyls (PCB/PCT),
- -mercury containing components, such as switches or backlighting lamps,
- ---batteries.
- —printed circuit boards of mobile phones generally, and of other devices if the surface of the printed circuit board is greater than 10 square centimetres,
- -toner cartridges, liquid and paste, as well as colour toner,
- -plastic containing brominated flame retardants,
- -asbestos waste and components which contain asbestos,
- -cathode ray tubes,
- —chlorofluorocarbons (CFC), hydrochlorofluorocarbons (HCFC) or hydrofluorocarbons (HFC), hydrocarbons (HC),
- —gas discharge lamps,
- —liquid crystal displays (together with their casing where appropriate) of a surface greater than 100 square centimeters and all those back-lighted with gas discharge lamps,
- -external electric cables,
- —components containing refractory ceramic fibres as described in Commission Directive 97/69/EC of 5 December 1997 adapting to technical progress for the 23rd time Council Directive 67/548/EEC on the approximation of the laws, regulations and administrative provisions relating to the classification, packaging and labelling of dangerous substances,
- —components containing radioactive substances with the exception of components that are below the exemption thresholds set in Article 3 of and Annex I to Council Directive 96/29/Euratom of 13 May 1996 laying down basic safety standards for the protection of the health of workers and the general public against the dangers arising from ionizing radiation,
- —electrolyte capacitors containing substances of concern (height > 25 mm, diameter > 25 mm or proportionately similar volume). These substances, mixtures and components shall be disposed of or recovered in compliance with Directive 2008/98/EC.



9. Recommendations for WEEE Directive Compliance

- (1) To make the product comply with the reuse/recycling/recovery target required under WEEE Directive (2012/19/EU) and other EU waste regulation, the applicant company should consider the product they design can be easily reused and recycled by selecting recyclable materials and components.
- (2) To make the product easily dismantled, less the disassembling time, the applicant company should design the product for easy disassembly by choosing easy separate techniques, avoiding the utilizing embedded components, designing the separable procedure.
- (3) The product should be subjected to the RoHS Directive (2011/65/EU), restricting using hazardous substance. In addition, the materials selected to design should consider the dangerous substance regulated or list under other environmental specifications, as Regulation (EC) 1907/2006(REACH), 67/548/EEC, etc.
- (4) In case that a product have new design, or employ materials or components, then the product should need to be reassessed and retested in accordance with the WEEE Directive for reuse/recycle/recycling target and RoHS for restricted substances requirement.
- (5) The applicant company should take attention to the future possible update concerning the WEEE Directive and related requirement.

****End of Report****

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of NTEK, this report can't be reproduced except in full.